

# PRODUCT SPECIFICATION

<b>Product System:</b>	<b>Health Based Building Installation of Vinyl Flooring to a Magnum Board Substrate</b>
<b>Project Reference:</b>	
<b>Site Address:</b>	
This Specification is intended for the above listed products and all products must be installed in accordance to this product specification and the Technical Data Sheet (TDS) of the products listed herewith.	

## 1. PRIMER

a. **Trade Name:** [Eco Prim Grip](#)

Multi-purpose, ready-to-use bonding promoter primer or render, smoothing and levelling compounds and adhesives.

## 2. SMOOTHING COMPOUND

a. **Trade Name:** [Planiprep SC](#)

A high performance fibre reinforced rapid drying skim coating compound.

## 3. VINYL ADHESIVE

a. **Trade Name** [Ultrabond Eco VS90 Plus](#)

Hard set, highly shear resistant, wet-bed dispersion adhesive, specific for PVC, rubber flooring and wall coverings on absorbent substrates.

## 4. **Magnum Board Substrate**

- a. The substrate should be free of all dust, oil, wax, paint or other surface contaminants before the commencement of the application of the primer

## 5. **Installation**

- a. After sufficient preparation of the Magnum Board substrate the installation of the primer may commence with the utilisation of Eco Prim Grip

The information in this Specification is consistent with the information given in the Product Technical Data Sheets (TDS). If further information is required, MAPEI recommends referring to the Product TDS, or seeking advice from MAPEI NEW ZEALAND LTD.

The information given in this Specification relating to the application and use of MAPEI products is given in good faith based on MAPEI's current knowledge and experience of the product when appropriately stored, handled and applied under recommended conditions as per the information in the Product TDS. In practice, the difference in application conditions, substrates, materials, and site environments are such that no guarantee in respect of consumption, or fit for a particular purpose can be concluded either from the information given in this specification, or any other written or verbal recommendations. The Applicator of the product must assess the substrate and the product's suitability for the intended application and final service provision of the product or product system.



- b. Once the Eco Prim Grip has dried, the installation of one to two coats of skim coating compound may commence with the utilisation of Planiprep SC.
- c. After sufficient curing of the skim coat, installation of the Vinyl can then be carried out utilising Ultrabond Eco VS90 Plus. A 1.5 x 1.5mm V notched trowel is the recommended size not withstanding a 100% contact of the adhesive bed to the Vinyl is required.

## Warranty

MAPEI NEW ZEALAND LTD (MAPEI NZ LTD) provides product warranties, if the products are installed in accordance with the products Technical Data Sheet (TDS) plans, specifications, and complies with the relevant provisions of the New Zealand [building code](#).

MAPEI NZ LTD warrants that the product/s when prepared and applied in accordance with the TDS will have the properties and characteristics set out in the TDS and will retain these properties and characteristics for the duration of the listed Warranty Period.

The Applicator of a MAPEI product is not an agent or employee of MAPEI and therefore MAPEI takes no responsibility and assumes no liability for their workmanship.

The applicator of the product must assess the substrate and the product/s suitability for the intended application and final service provision of the product.

MAPEI NZ LTD warranties ***do not*** cover installation, workmanship or product mixing and preparation aspects which is the sole responsibility of the applicator who is not an officer, agent, servant, or employee of MAPEI NZ LTD.

It is the sole responsibility of the product applicator to store the product/s, prepare the substrate, prepare, mix, and apply the product/s in accordance to the product/s TDS.

Information given relating to the application and use of MAPEI products is given in good faith based on MAPEI's current knowledge and experience of its products when they are appropriately stored, handled and applied under recommended conditions according to the information in the product/s TDS.

A full list of all product warranty terms and conditions is available upon request.

### MAPEI NZ LTD

**Peter Smith**

**Resilient Line Technical Sales**

**Email: [peter.smith@mapei.co.nz](mailto:peter.smith@mapei.co.nz)**

**Mob: +64 292 950 505**

**DD: 09 921 1996**

**[www.mapei.co.nz](http://www.mapei.co.nz)**

Spec. Name:	Installation of Vinyl Flooring to a Magnum Board Substrate	Version:	1	Release date:	21/09/2018
Compiled by:	Peter Smith	Date:	21/09/2018	Checked:	Peter Smith
					Page 2 of 2