

PRE-CHECKLIST

FOR PLASTERING MAGNUM BOARD WALLBOARD WITH FX SUPER BASE COAT X & PROFORM MULTI

Note: It is the responsibility of the plasterer to inspect their workplace prior to using FX Plaster to ensure the installed work will meet the supplier's requirements. Notify the owner / general contractor of any concerns prior to plastering.

Company Name:		Job #
Address of Job:		
Name of contractor:		
Date		

Temperature between 18-25°C and 50% humidity	
FX product conditioned to room temperature	
FX product positioned away from contact with concrete	
floors Surface level and junctions butted up tight	
Surface clean	
Access & heights	
Health and Safety plan in place	
Pre-checklist completed and stored on record	

Tools and materials	
FX BASE COAT X	
PROFORM MULTI	
Fibre Fuse Tape	
Sheet Rock Paper tape	
Sheet Rock Crack Free Paper Based Metal Trim	
150-200mm trowel / broad knife	
Hawk	
Stirrer	
220-grade sandpaper	
Thermometer and humidity reader	
Dust Mask	
Eye Protection	

POST-CHECKLIST

FOR PLASTERING MAGNUM BOARD WALLBOARD WITH FX SUPER BASE COAT X & PROFORM MULTI

Note: It is the responsibility of the plasterer to inspect their workplace prior to using FX Plaster to ensure the installed work will meet the supplier's requirements. Notify the owner / general contractor of any concerns prior to plastering.

Company Name:		Job #
Address of Job:		
Name of contractor:		
Date:		

Walls are even and smooth, ready for painting, sanded where required	
Plaster is completely dry with conditions between 18-25°C and 50% humidity	
Waste material is removed or positioned for removal as non-toxic material	
Pre- and Post-Checklists are completed and stored on record	